

Battery Set Up & Warnings: Battery / Charger / Cable

Before you start using the Battery / Charger / Cable please read all instructions and warning below to ensure your safety and to ensure you get the best use out of the unit.



WARNING: DO NOT CHARGE THE BATTERY UNATTENDED. AS WITH ANY BATTERY, MAKE SURE THE TERMINALS ARE NOT SHORTED (CONNECTED BY A CONDUCTOR). A SHORTED BATTERY CAN CATCH FIRE, EXPLODE, AND POTENTIALLY CAUSE INJURY OR DEATH.

WARNING: BE ESPECIALLY CAREFUL WHEN TRANSPORTING THE BATTERY TO PREVENT SHORTS. IT IS RECOMMENDED THAT YOU REMOVE BOTH BLADE CONNECTORS FROM THE BATTERY AND BLOCK OR TAPE THE TERMINALS.

WARNING: NEVER REMOVE JUST ONE LEAD FROM THE BATTERY AS THIS LEAVES AN OPEN TERMINAL THAT CAN BE SHORTED.

WARNING: HOOKING UP THE BLADE CONNECTORS TO THE INCORRECT BATTERY TERMINAL WILL DAMAGE YOUR TB3. ALWAYS DOUBLE CHECK POLARITY! RED WITH RED, BLACK WITH BLACK.

WARNING: NEVER TOUCH METAL TO EXPOSED TERMINALS AS THIS WILL SHORT YOUR TERMINALS.

WARNING: THE BATTERY CHARGER IS MEANT ONLY TO CONNECTOR TO THE BATTERY. NEVER ATTEMPT TO CONNECT THE CHARGER TO THE TB3. THIS WILL DAMAGE THE TB3'S ELECTRONICS.



Set Up: Charge Battery

Step 1: Connect cables. Connect the cable to the battery. The **RED** blade connector connects with **RED** terminal on the battery, **BLACK** blade connector connects with **BLACK** terminal on the battery. Connect the male barrel connector of the cable to the female connector of the charger as seen to the right.

Step 2: Charge. Plug charger into a 110 Volt outlet. Please note that this charger is not compatible with 220 volts. The red LED will light when battery is being charged. When fully charged the green LED will illuminate.



Set Up: Powering Your TB3

With cable connected to the battery in the same orientation seen above, plug the male barrel connector into the TB3's female power port.

